

MultiSync® C651Q

LCD 65" Value Large Format Display

Datasheet



Stunning visibility for presentations and digital signage

Enhance your meeting and conferencing performance with stunning UHD resolution. Get high-end quality and reliability at a low total cost of ownership with long life-times.

Professional haze levels ensure great visibility without distracting reflections - along with brightness of up to 350 cd/m², the NEC MultiSync C Series meets the demands of today's meeting environments. Slim bezels and a modern appearance complement state of the art architecture to integrate perfectly into interior designs. With embedded office functionalities, start up ad-hoc meetings without the hassle of setting up the display environment first. Wake-up on connection is just one of many features which make meetings more efficient.

With the NEC MultiSync C651Q, presenters will feel confident during meetings of up to 8 participants whilst retailers and hospitality facilities can boost sales through digital signage.

Benefits

Future Ready with Open Modular Intelligence Expansion - upgrade the power of your display at any time by seamlessly integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute modules or signal interfaces for content feed and computing.

Modern and slim design - robust yet elegant allowing for an unobtrusive integration into any application and environment.

Mission-critical 24/7 ready operation - the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Ease of use and operation - smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.

Future-proof signal connectivity and processing - numerous native UHD resolution inputs with 60Hz refresh rate including DisplayPort, HDMI and an option slot for OPS Slot-in PCs, plus automatic upscaling to UHD for other signals, provide "pixel-free viewing" on a large scale.

Cost Saving Device Management - save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Product Information

Product Name	MultiSync® C651Q
Product Group	LCD 65" Value Large Format Display
Order Code	60004314

Display

Panel Technology	VA with Direct LED backlights
Active Screen Area (W x H) [mm]	1,428.5 x 803.5
Screen Size [inch/cm]	65 / 164
Brightness [cd/m ²]	350, 280 (shipment setting)
Contrast Ratio (typ.)	4000:1
Viewing Angle [°]	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	8 (grey-to-grey)
Haze Level [%]	Pro (44)
Supported Orientation	Landscape; Portrait

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 91.1
Vertical Frequency [Hz]	24 - 85

Resolution

Native Resolution	3840 x 2160			
Supported Resolutions	4096 x 2160; 3840 x 2160; 1920 x 2160; 1920 x 1200;	1920 x 1080; 1680 x 1050; 1600 x 1200; 1440 x 900;	1400 x 1050; 1280 x 1024; 1280 x 800; 1280 x 720;	1024 x 768; 800 x 600

Connectivity

Input Video Digital	2 x DisplayPort (with HDCP); 3 x HDMI (with HDCP)
Input Audio Analogue	1 x 3,5 mm jack
Input Audio Digital	2 x DisplayPort; 3 x HDMI
Input Control	1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232
Input Data	1 x microSD (MediaPlayer); 1 x USB 2.0 (Downstream); 1 x USB 2.0 (MediaPlayer); 1 x USB Type-B (Upstream); 2 x USB 2.0 (Compute Module, 1 x 5V/2A powered)
Output Video Digital	1 x DisplayPort (loop through: DisplayPort, OPS slot-in PC)
Output Audio Analogue	1 x 3,5 mm jack
Output Control	1 x LAN 100Mbit

Open Modular Intelligence

OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)
OPS Max. Current / Power Consumption [A / W]	4.7 / 75
Compute Module Slot	Slot Technology: Compute Module Slot (NEC proprietary standard)

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Human Sensor	Optional, external, 4-5m range, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable

NFC Sensor Integrated, 2cm range, free NEC Android App required

Electrical

Power Consumption Eco/max. [W] 200 Eco (shipment setting), 255

Power Savings Mode [W] < 0.5; < 2 (Networked Standby)

Power Management VESA DPMS

Environmental Conditions

Operating Temperature [°C] +0 to +40

Operating Humidity [%] 20 to 80

Mechanical

Dimensions (W x H x D) [mm] Without stand: 1,457 x 832 x 79

Weight [kg] 42

Bezel Width [mm] 13.2

VESA Mounting [mm] 4 holes; 400 x 400 (FDMI); 600 x 400 (FDMI); M8

Ingress Protection IP5x (front); IP2x (back)

MediaPlayer

Supported File Storage / File System MicroSDHC / FAT16, FAT32; USB 2.0 / FAT16, FAT32

Supported Image Formats JPG (baseline, progressive, RGB, CMYK); max. resolution 5000 x 5000; PNG (interlace, alpha channel); max. resolution 4000 x 4000

Supported Video Formats MP4 / MOV / FLV (video H.264, audio MP3, AAC); max. resolution 1080p at 30 Hz, 1080i at 60 Hz; MPG (video mpeg1/2, audio mpeg audio layer2/3, AAC-LC); MP @ ML, MP @ HL; WMV (video H.264, wmv advanced L3, wmv simple / main, audio mp3 wmv std); max. resolution 1080p at 30 Hz, 1080i at 60 Hz

Supported Audio Formats MP3 (MP3); max. bit-rate 320 kBit/s; WAV (LPCM); max. 48 kHz sampling

Available Options

Accessories Feet (ST-801); Speaker (SP-654QSM, SP-TF1); Trolley (PD02MHA, PD03MHA, PDMHM-L); Wall mount (PDW T XL-2)

Compute Module Slot NEC Compute Module; Raspberry Pi Compute Module 1 and 3

OPS Slot HDBaseT receiver; Intel® Atom, Celeron and Core CPUs; OPS-2C Quad 3G SDI

Green Features

Energy Efficiency Ambient light sensor; Annual energy consumption: 257 kWh (based on 4 operating hours per day); Carbon savings meter; ECOMode; Energy efficiency class: B; Local dimming

Additional Features

Special Characteristics 12-bit Look Up table; Ambient Light Sensor; AMX NetLinx Support; ASCII Control Commands; Auto ID assignment; Auto tiling function; Automated Email Alert; CEC Support; Cisco Webex Kit compatible; Crestron Connected Support; DICOM Simulation; Display Browser Control; Emergency Notification; HDMI with UHD at 60 Hz; HDR Gamma Support (HLG, PQ); KeyGuide; MediaPlayer with Browser Control; NaViSet Administrator 2; OmniColor Control; OSD rotation for portrait mode; PIN as theft protection; PJLink Support; Powered USB-Port; Removable Logo; Scheduler; Slim LED Indicator; SNMP Support; TileMatrix (10 x 10); User readable log function

Colour Versions optional coloured overframes

Safety and Ergonomics CE; EAC; EMC Class B; FCC; SASO; TÜV GS; UL/C-UL or CSA; VCCI

Pixel Failure Class ISO 9241-307, Class 1

Audio	Integrated Speakers (10 W + 10 W); Optional Speakers (15 W + 15 W)
Shipping Content	CD-ROM (User Guides/Manuals); Display; DisplayPort Cable; Remote Control; USB cable
Warranty	3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension
Operating Hours	24/7



CE



TÜV GS



VCCI

This document is © 2020 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 23.09.2020