

## PANEL

Screen Size	65"
Resolution	3,840 x 2,160 (UHD)
Brightness(Typ.,cd/m <sup>2</sup> )	350

## CONNECTIVITY

Input	HDMI (3) Side: 2, Rear: 1
Output	Audio (2) Digital Audio Out, Optical
External Control	RS232C In (Phone Jack Type), RJ45 In

## PHYSICAL SPECIFICATION

Bezel Width	17.9 mm (T/L/R), 22.3 mm (B)
Monitor Dimension (W x H x D)	1,468 x 854 x 89.9 mm
Weight (Head)	21.0 kg
Carton Dimensions (W x H x D)	1,600 x 970 x 190 mm
Packed Weight	28.6 kg
VESA™ Standard Mount Interface	300 x 300 mm

## ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10% to 80%

## POWER

Power Supply	100-240V~, 50/60Hz
--------------	--------------------

---

Power Type	Built-In Power
------------	----------------

---

## POWER CONSUMPTION

Typ.	174 W
------	-------

---

Max	194 W
-----	-------

---

## STANDARD(CERTIFICATION)

Safety	CB
--------	----

---

EMC	CE
-----	----

---

ErP	Yes (Class A)
-----	---------------

---

## CERTIFICATION

Safety	IEC 60065:2014
--------	----------------

---

## MEDIA PLAYER COMPATIBILITY

OPS type compatible	No
---------------------	----

---

External Media player Attachable	No
----------------------------------	----

---

## SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
-----------------------------	---------------

---

Control and Monitoring Software	SuperSign Control+
---------------------------------	--------------------

---

## ACCESSORY

### Basic

Remote Controller (2ea Batteries Included), Regulation Book,  
Phone to RS232C Gender

---

## COMPLIANCE INFORMATION

[ENERGY LABEL\(65UL3E-B\)](#)

---

[PRODUCT FICHE\(65UL3E-B\)](#)

---

[WEB INFO\(65UL3E-B\)](#)

---

[\*\*MORE COMPLIANCE INFORMATION\*\*](#)

---