

Model

Panel

Screen Size
Panel Technology
Backlight Type
Brightness (typical)
Native Resolution
Contrast Ratio (typical)
Dynamic Contrast Ratio
Life Time (typical)
Response Time (typical)
Active Area (H x V)
Pixel Pitch (H x V)
Viewing Angle
Color Value
Screen Treatment
Haze Level
Refresh Rate
Front Type
Orientation
Operation Hours
Area of Usage

Built-in System

Mainboard Model

Monitor Connectivity

RGB Input
RGB Output
Video Input
Video Output
Audio Input
Audio Output
External Control
External Sensor

Environmental Conditions

Operating Temperature
Operating Humidity

Power

Power Supply

Power Consumption

Typical

Maximum

Deep Standby

Mechanical Features

Size

Shipping Size

Weight (kg)

Shipping Weight

Vesa Mounting Size

Bezel Width

Features

Main Features

Speaker

Accessory

Standard

Mounting Kit

Certification

Safety

EMC

CE

WW55B/2HB

55"

IPS

DLED

500 cd/m²

1920x1080

1100 : 1 (TBD)

500000 : 1

100000 hrs

8 ms

1212.2(H) x 683(V) mm

0.630 x 0.630

178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10

1.06 B (10-bit)

3H

28%

60 Hz

Extra narrow bezel

Horizontal / Vertical

24/7 Panel

Indoor

17MB135VS

VGA(DE-15F)

N/A

2xHDMI2.0, 2xUSB2.0, USB2.0(Internal)

HDMI2.0

Line In L/R

Headphone, Optic SPDIF

RS232(DE-9F), Ethernet(RJ45), Service(RJ12)

RJ12

+50°C / 0°C

90%

110 VAC - 240 VAC

138 W

260 W

0.5W

1212.2 (W) x 105.4 (D) x 683 (H) mm

1366 (W) x 277 (D) x 836 (H) mm

27 kg

37 Kg

400 x 600

1.8 mm

Videowall setup with Daisy-Chain, Open Content Management Support, Manual Fine Color Calibration, Videowa

N/A

QSG, IB, Power Cord, Remote Control, RC Battery, Display Port Cable, USB to Rs232 Converter

Standard

Yes

Yes

Yes

II Scheduler, Auto-Launch, Auto-switch on Failover, Panel Lock